



- NOTE:
1. CABLE: {(28AWG X 3COAX, EACH COAX SPIRAL SHIELDED, 75Ω, COLOR CODE: RED, GREEN, BLUE ) + (24AWG X 2PAIRS + 24AWG X 4C)}, OVERALL: AL-FOIL AND BRAID(85%MIN) SHIELDED WITH A DRAIN WIRE, UL2919, BLACK( BK) PVC JACKET.SLOT  $\varnothing 8.5 \pm 0.15$ MM.
  2. CONNECTOR: P1 & P2: HIGH DENSITY D-SUB 15PIN MALE: THE 9TH UNLOADED, SOLDER TYPE, GOLD FLASH CONTACTS, BLACK PBT INSULATION.
  3. BLACK METAL SCREW.(MATERIAL: STEEL)
  4. THUMB SCREW TO BE MOLDED BLACK ( BK) ABS.
  5. SHIELDING: COPPER-FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
  6. ALL HOOD MOLDED BLACK( BK) PVC.
  7. TESTING: 100% ELECTRICAL TEST: 1M OHM/MAX INSULATION RESISTANCE. 3 OHM/MIN CONTACTOR AT DC 300V

