



HDD15M		PIN OUT	HDD15F	
1	▲	RED COAX	▲	1
6	▲	RED GND	▲	6
2	▲	GRAY COAX	▲	2
7	▲	GRAY GND	▲	7
3	▲	BLUE COAX	▲	3
8	▲	BLUE GND	▲	8
4	⚡	BROWN	⚡	4
13	⚡	BRN/BLK	⚡	13
5	⚡	ORANGE	⚡	5
10	⚡	ORG/BLK	⚡	10
11	⚡	RED	⚡	11
15	⚡	RED/BLK	⚡	15
12	⚡	YELLOW	⚡	12
14	⚡	YEL/BLK	⚡	14
SHELL			SHELL	

NOTE:

- CABLE: UL2919 1354(S)7/0.127TA\*3C+7/0.127TA\*4PR+AB 85%  
 OD:4.5±0.15\*15.4±0.25 COLOR:P207 (W95052501)  
 MARKING: 9JAWM E101344-D STYLE 2919 VW-1 80°C 30V LOW  
 VOLTAGE COMPUTER CABLE Video Products Inc WWW.VPI.US
- CONNECTOR: HDD15P MALE NO 9 GOLD PLATED PIN  
 NICKEL SHELL, BLACK INSULATOR
- METAL: HDD15P SHORT TYPE, TIN PLATED
- THUMBSCREW: Q TYPE 4.5\*48.1 #4-40 UNC K782
- PVC: COLOR:V294, 45P, MOLDING TOOL:M<sub>2</sub><sup>1</sup>-D15-414

ELECTRONIC TEST:

- OPEN/SHORT/INTERMITTENCE: 100%.
- HI-POT: 300V AC/sec
- INSULATION RESISTANCE: 20MΩ (MIN)
- CONDUCTIVE RESISTANCE: 2Ω (MAX)



1275 Danner Drive Aurora, Ohio 44202  
 Tel: 1-800-626-7801 Fax: 330-562-1999  
 www.vpi.us sales@vpi.us