



HDMI CABLE 30AWG(A TO C)

PIN ASSIGNMENT:

HDMI/M	MINI	HDMI/M
3	3	TMDS data2-
1	2	TMDS data2+
2	1	TMDS data2 Shield
6	6	TMDS data1-
4	5	TMDS data1+
5	4	TMDS data1 Shield
9	9	TMDS data0-
7	8	TMDS data0+
8	7	TMDS data0 Shield
12	12	TMDS Clock-
10	11	TMDS Clock+
11	10	TMDS Clock Shield
17	13	DDC/CEC Ground
13	14	CEC
15	15	SCL
16	16	SDA
14	17	Reserved
18	18	+5V Power
19	19	Hot Plug Detect
SHELL	SHELL	SHELL

## ELECTRICAL CHARACTER:

- 100% OPEN&SHORT TESTING
- WITHSTANDING VOLTAGE:DC 300V 0.01Sec
- INSULATION RESISTANCE:10M Ohm(Min)
- CONDUCTIVE RESISTANCE:2 Ohm(Max)

5	OVERMOLD	PVC 70Pa BLACK UL94V-0	
4	INNERMOLD	PE LOW DENSITY	
3	MINI HDMI	MINI HDMI 15U*/AU BLACK SHELL G/F PLATED SOLDER TYPE WITH P.C.B	
2	HDMI	HDMI 15U*/AU BLACK SHELL G/F PLATED SOLDER TYPE WITH P.C.B	
1	HDMI CABLE	UL20276(1P*30#+AL+D+MYLAR)*4C+1P*30#+5C*30#+AL+B OD5.5mm JACKET:PVC BLACK 1.3REV Impedance:100ohm	
NO.	PART NAME	SPEC DESCRIPTION	REMAKE

**VPI VIDEO PRODUCTS INCORPORATED**

1275 Danner Drive Aurora, Ohio 44202

Tel: 1-800-626-7801 Fax: 330-562-1999

www.vpi.us

sales@vpi.us